

TRUCK & BUS TIRES



CHAO YANG
PREMIUM TYRES

CEAT

 **ROADSHRINE**

MEGA SUPER
ENGINEERED TO LAST TIRES

MIRAGE
TIRES

GRANDSTONE[®]
DRIVING TOGETHER

TRUCK & BUS TIRES



LOAD RANGE

LOAD RANGE	PLY RATING
A	2
B	4
C	6
D	8
E	10
F	12
G	14
H	16
J	18
L	20
M	22
N	24

SPEED RATING

CODE	KM/H	MPH
E	70	43
F	80	50
G	90	56
J	100	62
K	110	68
L	120	75
M	130	81
N	140	87
P	150	94

The **SPEED RATING** is the maximum speed tires can safely carry a load for a sustained amount of time in ideal conditions.

TRUCK & BUS TIRES



LOAD RATING - LOAD INDEX (LI)

LI	KGS	LBS
101	825	1819
102	850	1874
103	875	1929
104	900	1984
105	925	2039
106	950	2094
107	975	2150
108	1000	2205
109	1030	2271
110	1060	2337
111	1090	2403
112	1120	2469
113	1150	2535
114	1180	2601
115	1215	2679
116	1250	2756
117	1285	2833
118	1320	2910
119	1360	2998
120	1400	3086
121	1450	3197
122	1500	3307
123	1550	3417
124	1600	3527
125	1650	3658
126	1700	3748
127	1750	3858
128	1800	3968
129	1850	4079
130	1900	4299
131	1950	4299
132	2000	4409
133	2060	4542
134	2120	4674
135	2180	4806
136	2240	4938
137	2300	5071
138	2360	5203
139	2430	5357
140	2500	5512

LI	KGS	LBS
141	2575	5677
142	2650	5842
143	2725	6008
144	2800	6173
145	2900	6393
146	3000	6614
147	3075	6779
148	3150	6945
149	3250	7165
150	3350	7385
151	3450	7606
152	3550	7826
153	3650	8047
154	3750	8267
155	3875	8543
156	4000	8818
157	4125	9094
158	4250	9370
159	4375	9645
160	4500	9921
161	4625	10196
162	4750	10472
163	4875	10748
164	5000	11023
165	5150	11354
166	5300	11684
167	5450	12015
168	5600	12346
169	5800	12787
170	6000	13228
171	6150	13558
172	6300	13889
173	6500	14330
174	6700	14771
175	6900	15212
176	7100	15653
177	7300	16094

The **LOAD RATING** or **LOAD INDEX** indicates how much weight each tire can safely support



ROAD TYPE OR SURFACE CONDITION



LONG HAUL

- Long distance journey constant speed and less braking and accelerating
- Less fuel consumption and comfortable ride
- High Mileage performance



REGIONAL

- Shorter distance with frequent braking, accelerating and turning
- Improved road grip with maximum mileage
- Exceptional tough type



MIXED SERVICES

- Can be used for both on and off roads
- Heavy loads and outstanding durability
- Special protection against the damage caused by the road condition



ZC-Rubber successfully joins the ranks of global top 8 tire manufacturers in 2021. The annual revenue has reached \$4.528 billion. CHAOYANG is the earliest and most important brand in ZC-Rubber. As the leader of Chinese tire market, we also continuously get remarkable achievement in global market. Presenting high quality tires of bicycle, motorcycle, automobiles, light trucks, trucks, ATV, and trailers, we provide whole series of solutions demanded from customers worldwide.



ROAD TYPE OR SURFACE CONDITION					
POSITION	 Long Haul	 Regional	 Mixed Services		
 ALL POSITION	 AS668	 CR907	 CR950		
 STEER / TRAILER	 CR976A	 CR960A	 CB972	 CB995	 CM998
	 CM958	 CR931	 CM923	 CM988	 CB919
			 CR926 / CR926B / CR926D		
 DRIVE		 CM985		 MD738	



Long Haul



All Position

FEATURES & BENEFITS:

- Premium five-rib tread provides outstanding handling for steer application
- Decoupling grooves prevent uneven tread wear and ensure long tread life for long distance traveling
- Wide and deep tread guarantee longer mileage with affordable cost and remarkable value



AS668

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	H	18	149/146 L	15	7.5	41.5	10.9	7150	135	6610	135
11 R22.5	H	16	148/145 L	17	8.25	41.5	11	6940	123	6390	123
12 R22.5	J	18	152/149 L	18	9.0	42.7	11.9	7830	135	7160	135
295/80 R22.5	J	18	152/149 M	16	9.0	41.5	11.7	7830	131	7160	135



Long Haul



Steer / Trailer



CR976A

FEATURES & BENEFITS:

- Five ribs with four wide, straight grooves for precise handling and outstanding traction
- Stone ejector platforms prevent stones from lodging in grooves and drilling into belts
- Shallower tread depth helps to resist treadsquirm and irregular wear force for exceptionally long mileage

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	H	18	149/146 L	15	7.5	41.5	10.9	7150	135	6610	135
12 R22.5	J	18	152/149 L	16	9.0	42.7	11.8	7830	135	7160	135
275/80 R22.5	H	16	148/145 L	14	8.25	42.7	10.9	6940	130	6395	130



Regional



Drive



CM985

FEATURES & BENEFITS:

- Wide and deep tread enhances cost per mileage, driving stability and traction on highway application
- Open shoulder blocks improve traction on dry and wet road surface
- High blade density of tread design helps to provide even wearing
- Suitable for single axle vehicles

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12 R22.5	J	18	152/149 L	22	9.0	43.1	11.8	7830	135	7160	135



Regional



Steer / Trailer



CR960A

FEATURES & BENEFITS:

- Improved close shoulder helps improve even wear resulting in long tread life
- Straight simple rib pattern improves even wearing and efficient water evacuation for excellent wet traction and handling
- Cross rib sipes slice through water for solid control on wet roads

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
215/75R17.5	H	16	135/133J	13	6	30	8.3	4805	123	4540	123
235/75 R17.5	H	16	143/141 J	14	6.75	31.4	9.2	6005	128	5675	128
245/70 R19.5	H	16	136/134 M	13	7.50	33.0	9.8	4940	120	4675	120
285/70 R19.5	H	16	146/144 K	14	8.25	35.2	11.1	6610	123	6175	123
315/80 R22.5	J	18	136/134 M	13	7.50	33.0	9.8	4940	120	4675	120



Mixed Services



Drive



MD738

FEATURES & BENEFITS:

- Excellent traction for ON/OFF drive axle application
- Aggressive and optimum self-cleaning tread with lateral grooves provides remarkable performance in all weather conditions both on and off the road

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	16	148/145 L	21	8.25	41.9	11.0	6940	123	6390	123
295/80 R22.5	J	18	152/149 L	20	9.00	41.3	11.7	7830	131	7160	131



Mixed Services



Steer / Trailer



CB972

FEATURES & BENEFITS:

- Aggressive lug design with large blocks at tread center provides excellent traction and braking on rough roads with mud or gravel and is self-cleaning for ease of maintenance
- Applicable mining, logging, construction or rock and quarry operations with some very short on highway use possible
- Special tread compounds resist chipping and chunking in rugged off-road conditions

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 F	24	7.50	41.9	10.9	7160	135	6610	135
11.00 R20	J	18	152/149 F	25	8.00	43.1	11.5	7825	135	7165	135



Mixed Services



Steer / Trailer



CB995

FEATURES & BENEFITS:

- All-terrain all position tires designed for special service
- Special tread compounds resist chipping and chunking in rugged off-road conditions
- Open shoulder tread design help promote traction and floatation capacity on rough roads

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12.00 R20	J	18	154/151 K	20	8.50	44.3	12.4	8270	120	7610	120



Mixed Services



Steer / Trailer



CM923

FEATURES & BENEFITS:

- Drive axle tire applicable for rough road service
- Durable tire casing and wide tread enhance tire life
- Open lug design helps deliver super traction in wet and off-road conditions

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
315/80 R22.5	J	18	154/151 M	20	9.00	42.6	12.3	8270	120	7610	120



Mixed Services



Steer / Trailer



CM988

FEATURES & BENEFITS:

- Wide, deep tread helps provide long tread life in regional conditions
- Zigzag ribs ensure even wear and grip on wet, dry and snowy roads retreads

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	16	148/145 L	18	8.25	41.9	11.0	6940	123	6390	123



Mixed Services



Steer / Trailer



CM998

FEATURES & BENEFITS:

- Aggressive block design provides outstanding traction on rough roads
- Wide tread and special tread compounds resist chipping, chunking and tearing
- Durable tire casing for heavy loads
- Applicable for low speed use. Maximum speed shall be limited to 50km/hr in summer

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 J	18	7.50	41.5	10.9	7160	135	6610	135



CR926 / CR926B / CR926D



Mixed Services



Steer / Trailer

FEATURES & BENEFITS:

- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11.00 R20	J	18	152/149 K	16	8.00	42.7	11.5	7825	135	7165	135
12.00 R20	J	18	154/151 K	18	8.50	44.3	12.4	8270	120	7610	120
12.00 R24 (B)	L	20	160/152 K	19	8.50	48.8	12.4	9920	131	9090	131
11 R22.5 (D)	H	16	148/146 M	17	8.25	41.5	11.0	6940	123	6390	123
12 R22.5	J	18	152/149 L	16	9.00	42.7	11.8	7830	135	7160	135
295/80 R22.5 (D)	J	18	152/149 L	16	9.00	41.1	11.7	7830	131	7160	131
315/80 R22.5 (B)	J	18	156/150 L	17	9.00	42.4	12.3	8270	120	7610	120



Long Haul



All Position



CR907

FEATURES & BENEFITS:

- Improved closed shoulder helps to improved even wear resulting in long tread life
- Cross rib sipes slice through water for solid control on wet roads

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00R16	G	14	118/1141	11	5.50F	30.5	7.8	2908	111	2600	111



Regional



All Position

FEATURES & BENEFITS:

- Tread pattern provides extended even wear and offers excellent wet traction
- Advanced compound promotes mileage before removal for long tyre life



CR950

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
9.5 R17.5	H	18	132/130 L	17	6.75	33.2	9.5	4409	120	4299	120



Long Haul



Steer / Trailer

FEATURES & BENEFITS:

- Multiple gripping edges slice through water and road films for a solid grip
- Four wide continuous rib design help resist tread squirm and heel-and-tow wear for exceptionally long tread life
- Three circumferential grooves help deliver all-season traction on wet or dry road
- Closed shoulder design helps promote even wear throughout the tyre life



CM958

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
215/75R17.5	H	16	135/133J	13	6	30	8.3	4805	123	4540	123



Long Haul



Steer / Trailer

FEATURES & BENEFITS:

- Wide base multi-rib trailer tyres with durable compound to deliver excellent value
- Strong casing structure offers multiple retreads and lower total cost
- Improved tread design promises outstanding stability with optimized footprint and better tyre life



CR931

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
385/65R22.5	J	18	158L(160K)	15.5	11.75	42.2	15.3	9370	125	-	-



Mixed Services



Steer / Trailer



CB919

FEATURES & BENEFITS:

- Aggressive lug design with large block at tread center designed for mining, rock and quarry operations
- Wide tread and special tread compounds resist chipping, chunking, and tearing
- Stone rejector platform prevents trapped stones from punching deeper and piecing belt

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12.00 R20	J	18	154/151 F	25.5	8.50	44.7	12.4	8270	120	7610	120
12 R22.5	J	18	152/149 F	24	9.00	43.1	11.5	7830	135	7160	135









Founded in 1958, CEAT is one of India's leading tyre brands and the flagship company of the RPG GROUP. Driven by the purpose of helping the world move safely and smartly, CEAT provides world-class products and services across 110+ countries.



TRUCK & BUS TIRES

VISAYAS AND
MINDANAO
DISTRIBUTION
ONLY

PPC Asia
COMPARE US

		ROAD TYPE OR SURFACE CONDITION	
POSITION	 Long Haul	 Regional	 Mixed Services
 ALL POSITION	 WINLOAD-AV		
 STEER / TRAILER	 BULAND MILE XL RIB	 MILE-XL RID	 WINMILE RID
 DRIVE	 FM SUPER		 BULAND MILE XL TUG
 DRIVE / TRAILER			 HCL SUPER

VISAYAS AND MINDANAO DISTRIBUTION ONLY



BULAND
MILE XL RIB



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Less rolling resistance
- Better fuel mileage
- New generation carbon
- Buttons for faster heat dissipation
- Turbo ventilated buttress

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00-15	F	12	113/109 K	14	5.50 F	29.9	7.9	2535	90	2271	90
7.00-16	G	14	118/114 M	14	5.50F	30.5	7.9	2910	110	1601	110
7.50-16	H	16	122/118 M	13	6.00G	31.7	8.5	3307	110	2910	110
8.25-16	H	16	128/124 K	19	6.50 H	34.3	9.3	3968	110	3527	110

VISAYAS AND MINDANAO DISTRIBUTION ONLY



Mixed Services



Drive

FEATURES & BENEFITS:

- Less rolling resistance
- Better fuel mileage
- New generation carbon
- Buttons for faster heat dissipation
- Turbo ventilated buttress

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00-15	F	12	113/109 K	14	5.50 F	29.9	7.9	2535	90	2271	90
7.00-16	G	14	118/114 M	14	5.50F	30.5	7.9	2910	110	1601	110
7.50-16	G	14	122/118 M	13	6.00G	31.7	8.5	3307	110	2910	110
8.25-16	H	16	128/124 K	19	6.50 H	34.3	9.3	3968	110	3527	110

VISAYAS AND MINDANAO DISTRIBUTION ONLY



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Self cooling buttress control
- Improved durability
- Continuous shoulder rib
- Improved control
- Higher NSD
- Excellent mileage
- Better nylon casing
- Excellent retreadability

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.50-15	F	12	124/120 K	17	6.00 G	31.0	8.5	3527	100	3086	100
8.25-16	H	16	128/124 K	19	6.50 H	34.3	9.3	3968	110	3527	110
9.00-20	H	16	144/142 K	15.5	7.00	40.5	10.2	6173	130	5842	130

VISAYAS AND MINDANAO DISTRIBUTION ONLY



HCL SUPER



Mixed Services



Drive / Trailer

FEATURES & BENEFITS:

- Strong turn up area
- Enhanced tyre life
- Superior compounding
- Better loadability
- Optimal lug geometry
- Make it ideal for omnibus application

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
8.25-20	H	14	139/137 L	13.5	6.50	38.3	9.3	5357	130	5071	130
9.00-20	H	16	144/142 K	15.5	7.00	40.5	10.2	6173	130	5842	130
10.00-20	J	18	149/146 K	20.5	7.50	41.9	10.9	7165	130	6614	130
11.00-20	J	18	152/149 K	21	8.00	43.1	11.5	7826	130	7165	130

VISAYAS AND MINDANAO DISTRIBUTION ONLY



FM SUPER



Long Haul



Regional



Drive

FEATURES & BENEFITS:

- Sinusoidal rib pattern
- Good mileage
- Continuous shoulder rib
- Improved control
- Better nylon casing
- Excellent retreadability
- Optimized NPD better for On/Off road application
- Value for money

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00-20	J	18	149/146 K	20.5	7.50	41.9	10.9	7165	130	6614	130

VISAYAS AND MINDANAO DISTRIBUTION ONLY



WINMILE RIB



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Stiffer and connected rib
- Higher mileage
- Cooler and low RR compound
- Increased fuel efficiency

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	16	146/143 K	21	8.25	41.5	11	6614	120	6008	120

VISAYAS AND MINDANAO DISTRIBUTION ONLY



WINLOAD-AW



Long Haul



Regional



All Position

FEATURES & BENEFITS:

- Stiffer and connected rib
- Higher mileage
- Cooler and low RR compound
- Increased fuel efficiency

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	16	146/143 K	21	8.25	41.5	11	6614	120	6008	120

VISAYAS AND MINDANAO DISTRIBUTION ONLY



We are a Large-scale integrated group company in China with more than 40 years history. Our group has rich capital and gets involved in five star hotel operation,real estate development, tire export and rubber import etc.























We are one of the largest tire companies in China. The founder devotes all his life in tires and has profound understanding of the industry. We have established a very professional team to develop, manufacture, market the tires and serve our partners worldwide.



TRUCK & BUS TIRES



ROADSHINE

		ROAD TYPE OR SURFACE CONDITION	
POSITION	 Long Haul	 Regional	 Mixed Services
 ALL POSITION			
 STEER / TRAILER	 RS618	 RS631	
	 RS618A	 RS612	 RS610
	 RS604	 RS615	
 DRIVE	 RS621A	 RS604A	 RS611
			 RS617
	 RS622		 RS619
			 RS606



ROADSHINE



Mixed Services



All Position



RS602

FEATURES & BENEFITS:

- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.
- Unique tread groove design effectively expels stones from tire groove.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00 R16	G	14	118/114 M	14	5.50F	30.5	7.9	2910	110	2601	110
7.50 R16	G	16	122/118 M	13	6.00G	31.7	7.5	3307	110	2910	110
8.25 R16	H	16	128/124 M	15	6.50H	31.7	9.3	3968	110	3307	110
8.25 R20	H	16	139/137 L	13.5	6.50	38.3	9.3	5357	130	5071	130
9.00 R20	H	16	144/142 K	15.5	7.00	40.5	10.2	6173	130	5842	130
10.00 R20	J	18	149/146 K	16.5	7.50	41.5	10.9	7165	130	6614	130
11.00 R20	J	18	152/149 K	17	8.00	42.7	11.5	7165	130	7165	130
12.00 R20	J	20	154/149 K	17.5	8.50	44.3	12.4	8267	110	7165	110
11 R22.5	H	18	146/143 M	15	8.25	41.4	11	6614	120	6008	120
12 R22.5	J	18	152/149 M	15	9.00	42.7	11.8	7826	130	7160	130
13R22.5	J	18	156/151 D	25.5	9.75	44.7	12.6	8820	128	7610	128
315/80 R22.5	L	20	157/154 K	23	9.00	42.3	12.2	9090	130	8270	130



ROADSHINE



Mixed Services



Drive



RS617

FEATURES & BENEFITS:

- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 F	23	7.50	41.5	10.9	7165	130	6614	130
11.00 R20	J	18	152/149 F	23	8.00	42.7	11.5	7826	130	7165	130
12.00 R20	J	20	154/151 F	23	8.50	44.3	12.4	8267	110	7165	110
11 R22.5	J	18	149/146 L	15.5	8.25	41.4	10.9	7160	135	6610	135
12 R22.5	J	18	152/149 M	15	9.00	42.7	11.8	7826	130	7160	130
315/80 R22.5	L	20	157/154 K	23	9.00	42.3	12.2	9090	130	8270	130



ROADSHINE



Regional



Drive



RS621A

FEATURES & BENEFITS:

- Suitable for short haul and low-speed trucks on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhance tire mileage for better economy.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12.00 R20	L	20	156/153 K	24	8.50	44.3	12.4	8818	130	8047	130



ROADSHINE



Long Haul



Drive



RS604A

FEATURES & BENEFITS:

- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 K	18	7.50	41.6	11	7165	130	6614	130
11 R22.5	H	18	146/143 K	16.5	8.25	41.5	11	6614	120	6008	120
9.5 R17.5	H	18	132/130 L	17	6.75	33.2	9.5	4409	120	4299	120
235/75 R17.5	H	18	132/129 M	16	6.75	31.4	9.2	4409	120	4079	120
245/70 R19.5	H	16	135/133 M	16	7.50	33.1	9.8	4806	120	4542	120
265/70 R19.5	J	18	143/141 J	16	7.50	34.2	10.3	6008	125	5677	125
12 R22.5	J	18	152/149 M	15	9.00	42.7	11.8	7826	130	7160	130



ROADSHINE



Long Haul



Drive



RS611

FEATURES & BENEFITS:

- Suitable for driving wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
275/70R22.5	M	16	148/145 M	16	8.25	31.7	8.25	3150	110	2900	110



ROADSHINE



Long Haul



Steer / Trailer



RS618

FEATURES & BENEFITS:

- Suitable for all wheel position of middle/long distance buses and steering and trailer position wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.
- Comfortable and safer driving experience, in addition to longer mileage.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.50 R16	G	14	122/118 M	13	6.00G	31.7	8.5	3307	110	2910	110
8.25 R16	H	16	128/124 M	15	6.50H	33.7	9.3	3968	110	3307	110
225/80 R17.5	H	16	123/122 L	16.5	6.75	31.6	11.9	3417	120	3307	120
245/70 R19.5	H	16	136/134 M	14	7.50	33.1	9.8	4939	120	4674	120
9.00 R20	H	16	144/142 K	16.5	7.00	40.1	10.2	6173	130	5842	130
10.00 R20	J	18	149/146 K	17.5	7.50	41.6	10.9	7165	130	6614	130
255/70 R22.5	H	16	140/137 L	14.5	7.50	36.6	10	5512	120	5071	120
275/70 R22.5	H	16	148/145 M	16	8.25	37.7	10.9	4938	130	4674	130
9 R22.5	G	14	136/134 L	15	6.75	38.2	9	4938	120	4674	120



ROADSHINE



Long Haul



All Position



RS620 +/A

FEATURES & BENEFITS:

- Suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- Specially designed for long distance transportation vehicles on good road conditions.
- Comfortable and safer driving experience, In addition to longer mileage.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	18	146/143 M	15	8.25	41.4	11	6614	120	6008	120
12 R22.5	J	18	152/149 M	15	9.00	42.7	11.8	7826	130	7160	130
295/80 R22.5	J	18	152/149 M	15	9.00	39.9	11.7	7385	120	6779	120



ROADSHINE



Long Haul



Trailer



RS631

FEATURES & BENEFITS:

- Suitable for middle/long distance on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
							SINGLE		DUAL	
							(lbs)	(psi)	(lbs)	(psi)
385/65R22.5	K	20	16.5	11.75	30.5	7.9	4500	110		110



ROADSHINE



Long Haul



Steer / Trailer



RS618A

FEATURES & BENEFITS:

- Suitable for wheel position of middle/long distance buses and steering and trailer position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.50 R16	G	14	122/118 M	13	6.00G	31.7	8.5	3307	110	2910	110
8.25 R16	H	16	128/124 M	15	6.50H	33.7	9.3	3968	110	3307	110
11 R22.5	H	18	146/143 M	15	8.25	41.4	11	6614	120	6008	120
275/80 R22.5	H	16	149/146 M	14	8.25	39.8	10.8	7165	123	6610	123



ROADSHINE



Mixed Services



Drive



RS610

FEATURES & BENEFITS:

- Deep and sturdy tread pattern for high mileage, stone & mud clearance.
- Stable center blocks minimize tread damage off road service.
- Optimum carcass construction for casing durability and uniform wear.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 K	17.5	7.50	41.6	10.9	7165	130	6614	130
12.00 R20	L	20	156/153 K	24	8.50	44.3	12.4	8818	130	8047	130



ROADSHINE



Long Haul



Trailer



RS612

FEATURES & BENEFITS:

- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 K	17.5	7.50	41.6	10.9	7165	130	6614	130
295/80 R22.5	J	18	152/149 M	15	9.00	39.9	11.7	7385	120	6779	120



ROADSHINE



Mixed Services



Drive



RS619

FEATURES & BENEFITS:

- Suitable for tipper trucks on tough road conditions such as mine and construction site.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11.00 R20	J	18	152/149 F	23	8.00	42.7	11.5	7826	130	7165	130



ROADSHINE



Regional



Drive



RS622

FEATURES & BENEFITS:

- Suitable for driving wheel position of vans on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12.00 R20	L	20	156/153 K	24	8.50	44.3	12.4	8818	130	8047	130



ROADSHINE



Long Haul



Trailer



RS604

FEATURES & BENEFITS:

- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12.00 R24	L	20	160/157 K	19	8.50	48.3	12.4	9920	131	9090	131
315/80 R22.5	J	18	154/151 M	16	9.00	42.3	12.3	8270	120	7160	120
315/80 R22.5	L	20	157/154 K	23	9.00	42.3	12.3	9090	130	8270	130



ROADSHINE



Mixed Services



Drive



RS606

FEATURES & BENEFITS:

- All position tire for construction site or on highway purpose.
- Unique sidewall design shows aggressive appearance and protects sidewall of tire from sharp impact.
- Dual tie-bar and wide foot print provide longer lasting tread life. Casing durability.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
12 R22.5	J	18	152/149 M	15	9.00	42.7	11.8	7826	130	7160	130
295/80 R22.5	H	16	150/147 M	18	9.00	41.1	11.7	7390	120	6780	120
295/80 R22.5	J	18	152/149 M	18	9.00	41.1	11.7	7830	131	7160	131



ROADSHINE



Long Haul



Trailer



FEATURES & BENEFITS:

- Suitable for all wheel position of middle/ long-distance buses and steering wheel position of trucks on good road conditions.
- 4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
9.5 R17.5	J	18	132/130 L	17	6.75	33.2	9.5	4409	120	4299	120
215/75 R17.5	H	16	135/133 J	13	6.00	30.2	8.3	4805	123	4540	123
235/75 R17.5	H	18	132/129 M	16	6.75	31.4	9.2	4409	120	4079	120
225/70 R19.5	G	14	128/126 L	15.5	6.75	31.9	11	3970	110	3750	110
265/70 R19.5	J	18	143/141 J	16	7.50	34.1	10.3	6005	123	5675	123



Jiangsu General Technology Co., Ltd. (stock code: 601500) is a holding subsidiary of Hongdou Group, a key enterprise group in Jiangsu Province and one of 120 national deepening reform pilot enterprises. It was listed on the Shanghai Stock Exchange in September 2016. It is a company focusing on various tires A modern high-tech enterprise with R&D, production and sales. The company has three major production bases in Wuxi, Thailand, and Cambodia. It has a stable and professional marketing team and a complete marketing network. It has developed more than 10,000 image stores and signboard stores across the country. It is one of the leading tire companies in China.

















The company pays attention to tire technology innovation, has established a technology center platform, an industrial design center and a nationally recognized laboratory, undertakes projects such as the national and Jiangsu Torch Plan, and conducts in-depth industry-university-research strategic cooperation with scientific research institutes, universities, and world-class suppliers, and has won 400 patents have been authorized, and the invention patents are in the forefront of the industry. It has won the China Rubber Industry Enterprise Innovation and Development Award, China Petroleum and Chemical Industry Technology Innovation Demonstration Enterprise and other awards. The company has well-known brands such as "Qianlima, Chituma, Qima, Tongyun, Xidatong, Heima", and is an AAA-level quality credit enterprise in Jiangsu Province.



MEGA SUPER
ENGINEERED TO LAST TIRES

MEGA SUPER

ENGINEERED TO LAST *TIRES*

		ROAD TYPE OR SURFACE CONDITION	
POSITION	 Long Haul  Regional	 Mixed Services	
 ALL POSITION	 MX306  MX707  MX206	 MX218  MX968	
 STEER / TRAILER	 MX216  MX115  MX118  MX168	 MX882  MX918	

MEGA SUPER

ENGINEERED TO LAST TIRES



MX115



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Excellent grip and steering performance at high speed.
- Stronger carcass for better durability.
- Longer mileage tread formula.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
6.50-14	D	8	99/95 J	9.5	4.5 J	27.8	7.1	1764	60	1521	60

MEGA SUPER

ENGINEERED TO LAST TIRES



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Excellent grip and steering performance at high speed.
- Stronger carcass for better durability.
- Longer mileage tread formula.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
6.50-16	F	12	110/105 J	11	5.50 F	29.6	7.3	2337	90	2039	90
7.50-15	G	14	121/119 J	12	6.00 G	31.0	8.5	3197	100	2998	100

MEGA SUPER

ENGINEERED TO LAST TIRES



MX306



Long Haul



Regional



All Position

FEATURES & BENEFITS:

- Longer mileage tread formula.
- Stronger carcass for better durability.
- With good heat abstraction and great composition performance, suitable for overloading and low-speed driving on bad road condition.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00-15	F	12	113/109 K	13	5.50 F	30.0	7.9	2535	90	2271	90
7.50-15	G	14	121/119 J	13	6.00 G	31.0	8.5	3197	100	2998	100
7.00-16	G	14	118/114 K	13	5.50 F	30.7	7.9	2910	100	2601	100
7.50-16	H	16	122/118 K	13	6.00 G	32.3	8.5	3527	105	3086	105

MEGA SUPER

ENGINEERED TO LAST TIRES



MX218



Mixed Services



All Position

FEATURES & BENEFITS:

- Adopting the design of deep pattern and large pattern block, high grip ability, puncture resistance.
- With good heat abstraction and great composition performance, suitable for overloading and low-speed driving on bad road condition.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
5.00-12	E	10	88/86 K	12	3.50 B	23.0	5.6	1235	70	1168	70
6.50-14	D	8	99/95 J	9.5	4.50 J	27.8	7.1	1764	60	1521	60
6.50-16	D	12	110/105 J	11	5.50 F	29.6	7.3	2337	90	2039	90
7.00-15	F	12	113/109 K	14	5.50 F	29.9	7.9	2535	90	2271	90
7.00-16	G	14	118/114 K	15	5.50 F	30.9	7.9	2910	100	2601	100
7.50-15	H	16	124/120 K	17	6.00 G	31.0	8.5	3527	100	3086	100
7.50-16	H	16	122/118 K	19	6.00 G	32.3	8.5	3527	105	3086	105
8.25-16	H	16	128/124 K	19	6.50 H	34.3	9.3	3968	110	3527	110

MEGA SUPER

ENGINEERED TO LAST TIRES



Mixed Services



All Position

FEATURES & BENEFITS:

- High durable tread design to carry extra load.
- Cut and puncture resistant tread compound.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
5.00-12	E	10	88/86 K	12	3.50 B	23.0	5.6	1235	70	1168	70
7.00-16	G	14	118/114 K	18	5.50 F	30.9	7.9	2910	100	2601	100
7.50-16	H	16	122/118 K	19	6.00 G	32.3	8.5	3527	105	3086	105
8.25-16	H	16	128/124 K	19	6.50 H	34.3	9.3	3968	110	3527	110

MEGA SUPER

ENGINEERED TO LAST TIRES



MX707



Mixed Services



All Position

FEATURES & BENEFITS:

- Excellent impact resistant carcass.
- High bearing capacity.
- Cut resistance and long mileage tread compound for longer life.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
9.00-20	J	18	144/142 K	22	7.00	40.9	10.4	6007	130	5202	130
10.00-20	L	20	149/146 K	22	7.50	42.6	10.9	6779	130	6007	130
11.00-20	J	18	153/148 B	22	8.00	43.7	11.6	7396	130	6492	130

MEGA SUPER

ENGINEERED TO LAST TIRES



Long Haul



Regional



All Position

FEATURES & BENEFITS:

- Excellent grip and steering performance at high speed.
- Stronger carcass for better durability.
- Longer mileage tread formula.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00-15	F	12	113/109 M	12	5.50 F	29.5	7.9	2535	90	2271	80
7.00-16	G	14	118/114 K	13	5.50 F	30.7	7.9	2910	100	2601	100
7.50-16	H	16	124/120 K	17	6.00	33.1	8.5	3527	110	3086	110
8.25-16	H	16	28/124 K	12.5	6.50	33.9	9.3	3968	105	3527	105

MEGA SUPER

ENGINEERED TO LAST TIRES



Mixed Services



Steer / Trailer

FEATURES & BENEFITS:

- Rib & lug pattern for better steering and traction performance under bad road condition
- Unique tire shoulder design for cooler running performance
- Advanced groove geometry tread design with special tread compound for better cut and crack resistance.
- Reinforced carcass for better impact resistance retread factor.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
5.00-12	E	10	83/81 G	12	3.50 B	22.4	5.5	1073	60	1018	60
6.40/6.50-13	E	10	85/83 G	13	4.50 J	24.4	6.3	1135	50	1073	50
6.00-12	C	6	76/73 D	15	4.50 E	24.0	6.5	882	60	882	60
6.50-14	D	8	95/93 K	14.5	4.50 J	27.8	7.1	1764	60	1521	60

MEGA SUPER

ENGINEERED TO LAST TIRES



MX918



Mixed Services



Steer / Trailer

FEATURES & BENEFITS:

- High durable tread design to carry extra load.
- Cut and puncture resistant tread compound.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00-20	J	18	150/145 B	26.5	7.5	41.9	11.0	7385	130	6393	120
11.00-20	J	18	153/148 B	27	8.0	42.8	11.5	8047	130	6945	120
12.00-20	L	20	156/151 G	27.5	8.5	44.3	12.4	8818	130	7606	120

MEGA SUPER

ENGINEERED TO LAST TIRES



Mixed Services



Steer / Trailer

FEATURES & BENEFITS:

- Adopting the design of deep pattern and large pattern block, high grip ability, puncture resistance.
- With good heat abstraction and great composition performance, suitable for overloading and low-speed driving on bad road condition.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
8.25 -20	H	16	139/135 K	15.4	6.5	38.3	9.3	5357	115	4806	105

MEGA SUPER

ENGINEERED TO LAST TIRES



MX188



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Excellent grip and steering performance at high speed.
- Stronger carcass for better durability.
- Longer mileage tread formula.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
8.25 -20	H	16	139/135 K	15.4	6.5	38.3	9.3	5357	115	4806	105

MEGA SUPER

ENGINEERED TO LAST TIRES



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Suitable for driving on highway and generally paved road, the unique pattern design and formula, high quality raw material support, rib pattern are very popular.
- Excellent Structural Durability gives better load carrying capacity.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
5.00-12	E	10	83/81 G	12	3.50 B	22.4	5.5	1073	60	1018	60

MEGA SUPER

ENGINEERED TO LAST TIRES



MX168



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Suitable for driving on highway and generally paved road, the unique pattern design and formula, high quality raw material support, rib pattern are very popular.
- Excellent Structural Durability gives better load carrying capacity.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
5.00-12	E	10	83/81 G	12	3.50 B	22.4	5.5	1073	60	1018	60
6.40/6.50-13	E	10	85/83 G	13	4.50 J	24.4	6.3	1135	50	1073	50
6.00-12	C	6	76/73 D	15	4.50 E	24.0	6.5	882	60	882	60
6.50-14	D	8	95/93 K	14.5	4.50 J	27.8	7.1	1764	60	1521	60

MEGA SUPER

ENGINEERED TO LAST TIRES



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Suitable for driving on highway and generally paved road, the unique pattern design and formula, high quality raw material support, rib pattern are very popular.
- Excellent Structural Durability gives better load carrying capacity.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE					
								SINGLE		DUAL			
								(lbs)	(psi)	(lbs)	(psi)		

MEGA SUPER

ENGINEERED TO LAST TIRES



Long Haul



Regional



Steer / Trailer

FEATURES & BENEFITS:

- Excellent Structural Durability gives better load carrying capacity.
- Strong Casing and Side walls
- Great Mileage Performance
- Better retreads

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
9.00-20	H	16	144/142 K	22	7.00	40.9	10.4	6007	130	5202	130



Shandong Mirage Tyres Co., Ltd., is one of the famous tire manufacturers in China located in the tire capital town – Guangrao which is in Dongying city of Shandong province. Shandong Mirage Tyres Co., Ltd. specialized in the production of full range of radial tires by international advanced technology. The factory has two plants with an annual production capacity of 2 million for TBR and 6 million for PCR products.















Mirage insists on technical innovation and uses the national technical center as the development platform. It has the independent R & D capabilities for all the relevant technologies of radial tires , Mirage manufactures radial tires widely used in passenger car, SUV, truck and bus etc., with excellent performance, which are well-reputed all over China and more than 80 countries overseas.

Mirage owns the advanced R & D, production and testing equipments, furthermore, the excellent management team and specialized technology troops , which assures the outstanding and stable quality of its products. Many of Mirage's manufacturing equipment are imported from Europe and Japan. Mirage has built a strong quality assurance system and its products are accredited with certificates of ISO9001, ISO14001, OHSAS18001.IATF16949, CCC, DOT, ECE, GCC, INMETRO, BIS, SNI, SONCAP, etc.



MIRAGE
TRUCK & BUS **TIRES**

MIRAGE TIRES

POSITION	ROAD TYPE OR SURFACE CONDITION		
	 Long Haul	 Regional	 Mixed Services
 ALL POSITION			 MG011  MG702
 STEER / TRAILER	 MG111  MG660		
 DRIVE / TRAILER			 MG168  MG318  MG707  MG768

MIRAGE TIRES



Mixed Services



All Position



MG702

FEATURES:

- Three zigzag grooves
- Combination of rib and lug design

BENEFITS:

- Shoulder design with lugs
- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.00 R16	G	14	118/114 M	14	5.50F	30.5	7.9	2910	110	1601	110
7.50 R16	G	14	122/118 M	13	6.00G	31.7	8.5	3307	110	2910	110
8.25 R16	H	16	128/124 M	15	6.50H	33.7	9.3	3968	110	3307	110
8.25 R20	H	16	139/137 L	13.5	6.50	38.3	9.3	5357	130	5071	130
9.00 R20	H	16	144/142 K	15.5	7.00	40.5	10.2	6173	130	5842	130
10.00 R20	J	18	149/146 K	20.5	7.50	41.9	10.9	7165	130	6614	130
11.00 R20	J	18	152/149 K	21	8.00	43.1	11.5	7826	130	7165	130
12.00 R20	L	20	154/149 K	21.5	8.50	48.3	12.4	8267	110	7165	110
12 R22.5	J	18	152/149 L	18	9.00G	42.7	11.9	7830	130	7160	130

MIRAGE TIRES



Mixed Services



All Position



MG011

FEATURES:

- Three zigzag grooves
- Combination of rib and lug design

BENEFITS:

- Shoulder design with lugs
- Provide excellent anti-sideslipping performance and ensure excellent water evacuation
- Deliver outstanding traction and handling
- Provide excellent heat dissipation

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
315/80 R22.5	L	20	156/152 L	20	9.00	42.4	12.3	8818	125	7826	125

MIRAGE TIRES



Mixed Services



Drive / Trailer



MG707

FEATURES:

- Special tread compound
- Block pattern design
- Reinforced carcass and bead design

BENEFITS:

- Provide outstanding resistance to puncture and tearing
- Improved traction, driving and braking performance
- Ensure excellent handling and safe performance and provide outstanding loading capacity

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
10.00 R20	J	18	149/146 K	20.5	7.50	41.9	10.9	7165	130	6614	130
11.00 R20	J	18	152/149 K	21	8.00	43.1	11.5	7826	130	7165	130
12.00 R20	L	20	154/149 K	21.5	8.50	48.3	12.4	8267	110	7165	110
11 R22.5	H	16	146/143 K	21	8.25	41.5	11	6614	120	6008	120

MIRAGE TIRES



Mixed Services



Drive / Trailer



MG318

FEATURES:

- Lug and block pattern design
- Special tread compound
- Reinforced carcass and bead design

BENEFITS:

- Improved traction, driving braking performance
- Provide outstanding resistance to puncture and tearing
- Ensure excellent handling and safe performance and provide outstanding loading capacity

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
8.25 R20	H	16	139/137 L	13.5	6.50	38.3	9.3	5357	130	5071	130
9.00 R20	H	16	144/142 K	15.5	7.00	40.5	10.2	6173	130	5842	130
10.00 R20	J	18	149/146 K	20.5	7.50	41.9	10.9	7165	130	6614	130
11.00 R20	J	18	152/149 K	21	8.00	43.1	11.5	7826	130	7165	130
12.00 R20	L	20	154/149 K	21.5	8.50	48.3	12.4	8267	110	7165	110

MIRAGE TIRES



Long Haul



Regional



Steer / Trailer



MG111

FEATURES:

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Solid shoulder design

BENEFITS:

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	16	146/143 L	15	8.25	41.9	11.0	6614	120	6008	120

MIRAGE TIRES



Mixed Services



Drive / Trailer



MG768

FEATURES:

- Special tread compound
- Block pattern design
- Extra wide footprint with square shoulder

BENEFITS:

- Provide outstanding to puncture and tearing
- Provide excellent driving and braking force
- Enhanced stability and resistance to abrasion
- Ensure excellent and safe performance
- Provide outstanding loading capacity

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
315/80 R22.5	L	20	156/152 L	20	9.00	42.4	12.3	8818	125	7826	125

MIRAGE TIRES



Mixed Services



Drive / Trailer



MG168

FEATURES:

- Special tread compound
- Provide outstanding resistance to puncture and tearing
- Lug and block pattern design
- Improved traction, driving and braking performance

SUITABLE FOR:

- Drive and trailer position of dump truck, mining truck and concrete mixer
- Off road or loose surface condition including construction and mining sites.

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
7.50 R16	G	14	122/118 M	18	6.00G	32.1	8.5	3307	110	2910	110
8.25 R16	H	16	128/124 M	18	6.50H	34.1	9.3	3968	110	3307	110
8.25 R20	H	16	139/137 L	21	6.50	38.3	9.3	5357	130	5071	130
9.00 R20	H	16	144/142 K	21.5	7.00	40.5	10.2	6173	115	5842	115

MIRAGE TIRES



Long Haul



Regional



Steer / Trailer



MG660

FEATURES:

- Four wide circumferential grooves
- Siped rib and shoulder design
- Reinforced carcass and wide tread
- Specially designed compound

BENEFITS:

- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Ensure excellent handling and safe performance
- Deliver lower rolling resistance

SIZE	LOAD RANGE	PLY RATING	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	H	16	146/143 L	15	8.25	41.9	11.0	6614	120	6008	120
12 R22.5	J	18	152/149 L	18	9.00G	42.7	11.9	7830	130	7160	130



Founded in Qingdao, China, in 2001, Grandstone Tyre Corporation Limited is a professional and reputable tyre supplier. Together with its subsidiaries and 10 OEM manufacturers, Grandstone designs, manufactures, and supplies a full range of tyres including TBR, TBB, LTR, PCR, SUV, UHP, OTR, AGR, INDUSTRIAL tyres and inner tubes. The company has obtained certification of ISO/TS 16949, CCC, DOT, ECE, GCC, SONCAP, etc.

The company proudly exports Grandstone, Jumbo and associate brand tyres to more than 80 countries and regions throughout the globe. With advanced equipments, technology, strict quality-control system, efficient production and logistics management, Grandstone promises top-level quality and timely shipment.

With its values of honesty, responsibility and innovation, Grandstone is dedicated to driving business forward together with its partners.





Mixed Services



All Position



GT168

FEATURES & BENEFITS:

- All position application with zigzag pattern and 3 lines
- Applicable for various road surfaces even off-road
- Wider shoulder design and deep grooves ensure excellent directional stability, even wear and smooth ride
- Low heating up and longer mileage performance

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	J	18	146/143 L	15	8.25	41.5	11	6614	120	6008	120



Long Haul



Steer / Trailer



GT178+

FEATURES & BENEFITS:

- Straight five lines tread to increase the fuel-efficient.
- Special sipes in the groove side help fight irregular wear in steer position.
- Five ribs with four straight grooves for precise handling and low noise
- Low rolling resistance & noise emission.
- Applicable for highway and good road surface with high speed.

SIZE	LOAD RATING (LR)	PLY RATING (PLY)	SERVICE INDEX	TREAD DEPTH (mm)	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH (inch)	MAX LOAD CAPACITY @ COLD INFLATION PRESSURE			
								SINGLE		DUAL	
								(lbs)	(psi)	(lbs)	(psi)
11 R22.5	J	18	146/143 L	15	8.25	41.5	11	6614	120	6008	120